Technical specifications Haico PRO3

Dimensions

Table top including head support Head support of the table Table width excluding side panels Side panels - table Side panels - head support Wheels Padding thickness Weight	300 x 140 cm or 280 x 140 cm 40 x 85 cm or 30 x 85 cm 50 cm 46 x 37 cm 30 x 50 cm Ø15 cm 5 cm ca.550 kg
Adjustability	
Minimum height	34 cm
Maximum height	110 cm
C C	
Pelvic angle	+/-25°
Head support angle	+/-25°
Lateral angle	+/-12°
Head support	removable
Head support sides	removable
Side panels	removable
Control buttons	in front both sides
Loading	
Maximum load	1300 kg
Two speed lift :	
Lifting time normal	35 sec
Lifting time fast for unloaded table	15 sec

Electric equipment

Operation voltage12 VBattery service free lead acid cyclic application12 V 38 Ah ,10 yearsAutomatic battery charger output12 V 10 ACharger input110 V / 240 V AC / 50-60 HzBattery charging time6 hrsFull batteryca.30 liftsWireless remote controlca.30 liftsReadiness for transport unitTable can be used during charging

Surface coating

AL oxide blast , double paint

Equipment

Complete equipment as standard

Dystrybutor firmy HAICO na terenie Polski:



ul. Łazy 30A, 25 - 677 KIELCE tel: +48 41 346 18 11 e-mail: kosmed@kosmed.kielce.com www.kosmed.kielce.com

